


RECOMMENDED P. C. B. LAYOUT
UNSPECIFIED TOLERANCE: ±0.05
(COPPER-SIDED VIEW)

Specification:

1. Rating : DC 30V 0.5A.
 2. Contact resistance: ≤50mΩ.
After test: ≤100mΩ.
 3. Insulation resistance: ≥100MΩ (500VDC);
After test: ≥50MΩ.
 4. Withstand voltage: 500VAC .
 5. Insertion and extraction force: 3N~30N.
 6. life test: 5000cycles min.
 7. Operation temperature range: -20℃~70℃.
 8. Preservative temperature range: -40℃~85℃.
- Sign "▲" is importance dimension.



④	Ring spring	③④	2	Phosphor bronze T=0.25	03(JA-549)	Silver plating
③	Tip spring	②	1	Phosphor bronze T=0.25	02(JA-1319)	Silver plating
②	Earth spring	①	1	Stainless steel T=0.20	01(IP-548)	Silver plating
①	Housing		1	PBT		
NO.	DESCRIPTION	QTY	MATERIAL	PART NO.	PLATING	

凱鼎企業有限公司 KABOE ENTERPRISE CO.,LTD.		
Name Ø3.5mm PHONE JACK DIP R/A 4PIN TYPE		
Drawing No. PJ-2060-0491N		
APPD-	H-	D-R
General Tolerances: -X.XX± X.X±	Unit: mm	Scale: ROM